

TECHNICAL DATA SHEET: SL1400-LC-O / LL-O

Dimensions (closed product overall dimensions)	LC-O (short side removal) Width 839 mm Depth 347 mm Height 250 mm Weight 27.20 kg	LL-O (long side removal) Width 765 mm Depth 483 mm Height 250 mm Weight 26.25 kg
Hob Unit (straight valves with bypass Ø 0.36 mm)	1x AUXILIARY burner (AUX) Pn 1.00 kW - injector ø 0.50 mm - consumption 73.00 g/h 1x SEMIRAPID burner (SR): Pn 1.70 kW - injector ø 0.65 mm - consumption 124.0 g/h Total nominal power: 2.70 kW Total nominal consumption: 197.00 g/h	
Device Class (EN 484 4)	CLASS 1	
Device Category (EN 484 4.2)	CATEGORY I: ▪ I3 B/P (30), (50) ▪ I3+ (28-30/37)	
Gas Supply	PROPANE (G30) / BUTANE (G31) 28-30 mbar PROPANE (G30) / BUTANE (G31) 37 mbar	
Lighting	Hob unit: ▪ S (MANUAL) - using external igniter ▪ P (PIEZOELECTRIC) - Mechanically/manually operated piezoelectric igniter	
Gas Connection	Galvanised steel train: Ø 8 mm - 1 mm thick with flexible hose equipped with quick joint for outdoor gas valves	
Gas Capillaries	Copper capillary pipes: Ø 4 mm - 0.5 mm thick Aluminium capillary pipes: Ø 4 mm - 0.8 mm thick	
Water connection	Universal quick joint (male)	
Materials	<ul style="list-style-type: none"> ▪ Stainless steel AISI 304 ▪ Glass ▪ Aluminium ▪ Chromium-plated steel ▪ Zama ▪ Brass ▪ Copper ▪ Galvanised iron ▪ Aluminium alloy 	
Declaration of Conformity (GAR 2016/426/EC)	<ul style="list-style-type: none"> ▪ no asbestos ▪ there are no welds with melting point lower than 450°C ▪ flammable materials were not used ▪ materials comply with the requirements specified in Annex I, points 2 and 3.7 	